



CJB2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触点、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)

01表示三常开主触点、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)

11表示三常开主触点、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current

09:9A	25:25A	50:50A	95:95A
12:12A	32:32A	65:65A	
18:18A	40:40A	80:80A	

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)			
额定电流 Rated current	9A		额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	25A		额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	100万次 1 million times		机械寿命 Mechanical life	1000万次 10 million times
触点材质 Contact material	银触点 Silver contacts		导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil		防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5℃~+40℃,24小时内其平均温度不超过+35℃ -5℃~+40℃, the average temperature within 24 hours does not exceed +35℃			
重量 weight	1pcs/0.361KG 50pcs/1箱(box)			
产品型号 Product number	CJB2-0910		CJB2-0901	
单价 unit price				



CJB2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触点、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)

01表示三常开主触点、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)

11表示三常开主触点、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current

09:9A	25:25A	50:50A	95:95A
12:12A	32:32A	65:65A	
18:18A	40:40A	80:80A	

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)			
额定电流 Rated current	12A		额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	25A		额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	100万次 1 million times		机械寿命 Mechanical life	1000万次 10 million times
触点材质 Contact material	银触点 Silver contacts		导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil		防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5℃~+40℃,24小时内其平均温度不超过+35℃ -5℃~+40℃, the average temperature within 24 hours does not exceed +35℃			
重量 weight	1pcs/0.360KG 50pcs/1箱(box)			
产品型号 Product number	CJB2-1210		CJB2-1201	
单价 unit price				