



型号规格 Model specification	LRS-75-12	LRS-75-15	LRS-75-24	LRS-75-36	LRS-75-48
直流电压 DC voltage	12V	15V	24V	36V	48V
额定电流 Rated current	6A	5A	3.2A	2.1A	1.6A
当前范围 Current range	0~6A	0~5A	0~3.2A	0~2.1A	0~1.6A
额定功率 rated power	72W	75W	76.8W	75.6W	76.8W
波纹与噪音(max.) Note2 Ripple and noise (max.) Note2	120mVp-p	120mVp-p	150mVp-p	200mVp-p	200mVp-p
电压调整 范围 Voltage adjustment range	10.2~13.8V	13.5~18V	21.6~28.8V	32.4~39.6V	43.2~52.8V
耐电压 Note.3 Withstand voltage Note.3	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
线路调节 Note.4 Line adjustment Note.4	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
负载调节 Note.5 Load regulation Note.5	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
输入电压 Input voltage	100~240VAC				
频率范围 Frequency Range	47~63Hz				
效率(典型值) Suburb rate (typical value)	89%	89%	90%	91.5%	91.5%
交流电流(典型值) AC current (typical value)	1.4A/115VAC 0.85A/230VAC				
工作温度 Operating temperature	-20~+70℃		工作湿度 Working humidity		20-90%RH
尺寸 size	99X97X30mm (L*W*H)				
重量 weight	1pcs/0.230KG 100pcs/箱(box)				
单价 unit price					



型号规格 Model specification	LRS-100-12	LRS-100-15	LRS-100-24	LRS-100-36	LRS-100-48
直流电压 DC voltage	12V	15V	24V	36V	48V
额定电流 Rated current	8.5A	7A	4.5A	2.8A	2.3A
当前范围 Current range	0~8.5A	0~7A	0~4.5A	0~2.8A	0~2.3A
额定功率 rated power	102W	105W	108W	100.8W	110.4W
波纹与噪音(max.) Note2 Ripple and noise (max.) Note2	120mVp-p	120mVp-p	150mVp-p	200mVp-p	200mVp-p
电压调整 范围 Voltage adjustment range	10.2~13.8V	13.5~18V	21.6~28.8V	32.4~39.6V	43.2~52.8V
耐电压 Note.3 Withstand voltage Note.3	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
线路调节 Note.4 Line adjustment Note.4	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
负载调节 Note.5 Load regulation Note.5	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
输入电压 Input voltage	100~240VAC				
频率范围 Frequency Range	47~63Hz				
效率(典型值) Suburb rate (typical value)	88%	88.5%	90%	90.5%	91%
交流电流(典型值) AC current (typical value)	1.9A/115VAC 1.2A/230VAC				
工作温度 Operating temperature	-20~+70℃		工作湿度 Working humidity		20-90%RH
尺寸 size	129X97X30mm (L*W*H)				
重量 weight	1pcs/0.303KG 100pcs/箱(box)				
单价 unit price					