

导轨式开关电源系列

Rail type switching power supply series

BERM® 贝尔美



型号规格 Model specification	NDR-75-12	NDR-75-24	NDR-75-48
直流电压 DC voltage	12V	24V	48V
额定电流 Rated current	6.3A	3.2A	1.6A
电流范围 Current range	0~6.3A	0~3.2A	0~1.6A
额定功率 rated power	75W	75W	75W
波纹与噪音 Ripple and noise	80mVp-p	120mVp-p	150mVp-p
电压调整 范围 Voltage adjustment range	12~14V	24~28V	48~55V
电压精度 Voltage accuracy	±2.0%	±1.0%	±1.0%
线性调整率 Linear adjustment rate	±0.5%	±0.5%	±0.5%
负载调整率 Load adjustment ratio	±1.0%	±1.0%	±1.0%
效率 Suburb rate (typical value)	85.5%	88%	89%
输入电压 Input voltage	100~240VAC		频率范围 Frequency Range
			47~63Hz
启动、上升时间 AC current (typical value)	1200mS、60mS/230VAC 2000mS、60mS/115VAC(满载时/When fully loaded)		
交流电流 (Typ) AC current	1.45A/115VAC 0.9A/230VAC	浪涌电流 (Typ) Inrush current	20A/115VAC 35A/230VAC
工作温度 Operating temperature	-20~+70℃		工作湿度 Working humidity
			20~95%RH
尺寸 size	32X125.2X102mm (L*W*H)		
重量 weight	1pcs/0.51KG 28pcs/箱(box)		
单价 unit price			



型号规格 Model specification	NDR-120-12	NDR-120-24	NDR-120-48
直流电压 DC voltage	12V	24V	48V
额定电流 Rated current	10A	5A	2.5A
电流范围 Current range	0~10A	0~5A	0~2.5A
额定功率 rated power	120W	120W	120W
波纹与噪音 Ripple and noise	100mVp-p	120mVp-p	150mVp-p
电压调整 范围 Voltage adjustment range	12~14V	24~28V	48~55V
电压精度 Voltage accuracy	±2.0%	±1.0%	±1.0%
线性调整率 Linear adjustment rate	±0.5%	±0.5%	±0.5%
负载调整率 Load adjustment ratio	±1.0%	±1.0%	±1.0%
效率 Suburb rate (typical value)	85.5%	88%	89%
输入电压 Input voltage	100~240VAC		频率范围 Frequency Range
			47~63Hz
启动、上升时间 AC current (typical value)	1200mS、60mS/230VAC 2500mS、60mS/115VAC(满载时/When fully loaded)		
交流电流 (Typ) AC current	2.25A/115VAC 1.3A/230VAC	浪涌电流 (Typ) Inrush current	20A/115VAC 35A/230VAC
工作温度 Operating temperature	-20~+70℃		工作湿度 Working humidity
			20~95%RH
尺寸 size	40X125.2X113.5mm (L*W*H)		
重量 weight	1pcs/0.6KG 20pcs/箱(box)		
单价 unit price			