



型号/model	S-1000-12	S-1000-24	S-1000-36	S-1000-48
性能/performance				
直流电压 DC voltage	12V	24V	36V	48V
额定电流 Rated current	0~80A	0~42A	0~28A	0~21A
额定功率 rated power	1000W	1000W	1000W	1000W
波纹与噪音 Ripple and noise	150mVp-p	180mVp-p	180mVp-p	240mVp-p
进线稳定度 Incoming line stability	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability	±0.5%	±0.5%	±0.5%	±0.5%
效率 Suburban rate	80%	85%	85%	87%
直流电压可调范围 DC voltage adjustable range	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range	100-240VAC 50/60Hz			
冲击电流 impact current	冷启动电流 45A/230VAC Cold start current			
过载保护 Overload protection	105%~135% 切断输出, 自动恢复 105%~135% cut off the output, automatic recovery			
自动、上升、保持时间 Auto, rise, hold time	2000mS、50mS、20mS/230VAC 满负载/Full load			
工作温度 Operating temperature	-10~+50°C			
尺寸 size	291X132X68mm (L*W*H)			
重量 weight	1pcs/2.65KG 6pcs/箱(box)			
单价 unit price				



型号/model	S-1200-12	S-1200-24	S-1200-36	S-1200-48
性能/performance				
直流电压 DC voltage	12V	24V	36V	48V
额定电流 Rated current	0~100A	0~50A	0~33A	0~25A
额定功率 rated power	1200W	1200W	1200W	1200W
波纹与噪音 Ripple and noise	150mVp-p	180mVp-p	180mVp-p	240mVp-p
进线稳定度 Incoming line stability	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability	±0.5%	±0.5%	±0.5%	±0.5%
效率 Suburban rate	80%	85%	85%	87%
直流电压可调范围 DC voltage adjustable range	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range	100-240VAC 50/60Hz			
冲击电流 impact current	冷启动电流 45A/230VAC Cold start current			
过载保护 Overload protection	105%~135% 切断输出, 自动恢复 105%~135% cut off the output, automatic recovery			
自动、上升、保持时间 Auto, rise, hold time	2000mS、50mS、20mS/230VAC 满负载/Full load			
工作温度 Operating temperature	-10~+50°C			
尺寸 size	291X132X68mm (L*W*H)			
重量 weight	1pcs/2.65KG 6pcs/箱(box)			
单价 unit price				