

开关电源系列 Switching power supply series

BERM® 贝尔美



型号/model	S-250-5	S-250-12	S-250-15	S-250-24	S-250-36	S-250-48
性能/performance						
直流电压 DC voltage	5V	12V	15V	24V	36V	48V
额定电流 Rated current	0~45A	0~20A	0~16A	0~10A	0~6.7A	0~5A
额定功率 rated power	250W	250W	250W	250W	250W	250W
波纹与噪音 Ripple and noise	150mVp-p	150mVp-p	150mVp-p	150mVp-p	200mVp-p	240mVp-p
进线稳定度 Incoming line stability	±2%	±1%	±1%	±1%	±1%	±1%
负载稳定度 Load stability	±2%	±1%	±1%	±1%	±1%	±1%
效率 Suburban rate	74%	79%	79%	81.5%	84%	84%
直流电压可调范围 DC voltage adjustable range	±10%	±10%	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range	100-240VAC 50/60Hz					
冲击电流 impact current	冷启动电流 25A/115VAC 50A/230VAC Cold start current					
过载保护 Overload protection	105%~135% 切断输出, 自动恢复 105%~135% cut off the output, automatic recovery					
自动、上升、保持时间 Auto, rise, hold time	200mS、50mS、16mS/230VAC 满负载/Full load					
工作温度 Operating temperature	-10~+50°C					
尺寸 size	215X115X50mm (L*W*H)					
重量 weight	1pcs/1.15KG 20pcs/箱(box)					
单价 unit price						



型号/model	S-350-5	S-350-12	S-350-15	S-350-24	S-350-36	S-350-48
性能/performance						
直流电压 DC voltage	5V	12V	15V	24V	36V	48V
额定电流 Rated current	0~50A	0~29A	0~23.3A	0~14.6A	0~9.7A	0~7.3A
额定功率 rated power	350W	350W	350W	350W	350W	350W
波纹与噪音 Ripple and noise	150mVp-p	150mVp-p	150mVp-p	150mVp-p	150mVp-p	200mVp-p
进线稳定度 Incoming line stability	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
效率 Suburban rate	73%	83%	83%	85%	85%	86%
直流电压可调范围 DC voltage adjustable range	±10%	±10%	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range	100-240VAC 50/60Hz					
冲击电流 impact current	冷启动电流 25A/115VAC 50A/230VAC Cold start current					
过载保护 Overload protection	105%~135% 切断输出, 自动恢复 105%~135% cut off the output, automatic recovery					
自动、上升、保持时间 Auto, rise, hold time	200mS、50mS、20mS/230VAC 满负载/Full load					
工作温度 Operating temperature	-10~+50°C					
尺寸 size	215X115X50mm (L*W*H)					
重量 weight	1pcs/1.15KG 20pcs/箱(box)					
单价 unit price						