



型号/model	S-400-5	S-400-12	S-400-24	S-400-48
性能/performance				
直流电压 DC voltage	5V	12V	24V	48V
额定电流 Rated current	0~60A	0~33A	0~16.5A	0~8.3A
额定功率 rated power	400W	400W	400W	400W
波纹与噪音 Ripple and noise	100mVp-p	150mVp-p	150mVp-p	200mVp-p
进线稳定度 Incoming line stability	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability	±1%	±0.5%	±0.5%	±0.5%
效率 Suburban rate	73%	74%	81%	83%
直流电压可调范围 DC voltage adjustable range	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range	100-240VAC 50/60Hz			
冲击电流 impact current	冷启动电流 25A/115VAC 50A/230VAC Cold start current			
过载保护 Overload protection	105%~135% 切断输出, 自动恢复 105%~135% cut off the output, automatic recovery			
自动、上升、保持时间 Auto, rise, hold time	200mS、50mS、20mS/230VAC 满负载/Full load			
工作温度 Operating temperature	-10~+50°C			
尺寸 size	215X115X50mm (L*W*H)			
重量 weight	1pcs/1.15KG 20pcs/箱(box)			
单价 unit price				



型号/model	S-500-12	S-500-24	S-500-36	S-500-48
性能/performance				
直流电压 DC voltage	12V	24V	36V	48V
额定电流 Rated current	0~40A	0~20A	0~14A	0~10A
额定功率 rated power	500W	500W	500W	500W
波纹与噪音 Ripple and noise	100mVp-p	150mVp-p	150mVp-p	150mVp-p
进线稳定度 Incoming line stability	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability	±0.5%	±0.5%	±0.5%	±0.5%
效率 Suburban rate	83%	85%	86%	87%
直流电压可调范围 DC voltage adjustable range	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range	100-240VAC 50/60Hz			
冲击电流 impact current	冷启动电流 25A/115VAC 50A/230VAC Cold start current			
过载保护 Overload protection	105%~300% 切断输出, 自动恢复 105%~300% cut off the output, automatic recovery			
自动、上升、保持时间 Auto, rise, hold time	800mS、20mS、36mS/230VAC 满负载/Full load			
工作温度 Operating temperature	-10~+50°C			
尺寸 size	238X124X65mm (L*W*H)			
重量 weight	1pcs/1.35KG 12pcs/箱(box)			
单价 unit price				