

开关电源系列 Switching power supply series

BERM® 贝尔美



型号规格 Model specification	LRS-200-12	LRS-200-15	LRS-200-24	LRS-200-36	LRS-200-48
直流电压 DC voltage	12V	15V	24V	36V	48V
额定电流 Rated current	17A	14A	8.8A	5.9A	4.4A
当前范围 Current range	0~17A	0~14A	0~8.8A	0~5.9A	0~4.4A
额定功率 rated power	204W	210W	211.2W	212.4W	211.2W
波纹与噪音(max.) Note2 Ripple and noise (max.) Note2	150mVp-p	150mVp-p	150mVp-p	200mVp-p	200mVp-p
电压调整 范围 Voltage adjustment range	10.2~13.8V	13.5~18V	21.6~28.8V	32.4~39.6V	43.2~52.8V
耐电压 Note.3 Withstand voltage Note.3	±1.5%	±1.0%	±1.0%	±1.0%	±1.0%
线路调节 Note.4 Line adjustment Note.4	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
负载调节 Note.5 Load regulation Note.5	±1.0%	±0.5%	±0.5%	±0.5%	±0.5%
输入电压 Input voltage	100~240VAC				
频率范围 Frequency Range	47~63Hz				
效率(典型值) Suburb rate (typical value)	87.5%	88%	89.5%	89.5%	90%
交流电流(典型值) AC current (typical value)	4A/115VAC 2.2A/230VAC				
工作温度 Operating temperature	-20~+70℃		工作湿度 Working humidity		20-90%RH
尺寸 size	215X115X30mm (L*W*H)				
重量 weight	1pcs/0.643KG 100pcs/箱(box)				
单价 unit price					



型号规格 Model specification	LRS-250-12	LRS-250-15	LRS-250-24	LRS-250-36	LRS-250-48
直流电压 DC voltage	12V	15V	24V	36V	48V
额定电流 Rated current	20A	16A	10A	6.7A	5A
当前范围 Current range	0~20A	0~16A	0~10A	0~6.7A	0~5A
额定功率 rated power	250W	250W	250W	250W	250W
波纹与噪音(max.) Note2 Ripple and noise (max.) Note2	150mVp-p	150mVp-p	150mVp-p	200mVp-p	200mVp-p
电压调整 范围 Voltage adjustment range	10.2~13.8V	13.5~18V	21.6~28.8V	32.4~39.6V	43.2~52.8V
耐电压 Note.3 Withstand voltage Note.3	±1.5%	±1.0%	±1.0%	±1.0%	±1.0%
线路调节 Note.4 Line adjustment Note.4	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
负载调节 Note.5 Load regulation Note.5	±1.0%	±0.5%	±0.5%	±0.5%	±0.5%
输入电压 Input voltage	100~240VAC				
频率范围 Frequency Range	47~63Hz				
效率(典型值) Suburb rate (typical value)	87.5%	88%	89.5%	89.5%	90%
交流电流(典型值) AC current (typical value)	5.0A/115VAC 2.5A/230VAC				
工作温度 Operating temperature	-20~+70℃		工作湿度 Working humidity		20-90%RH
尺寸 size	215X115X30mm (L*W*H)				
重量 weight	1pcs/0.648KG 100pcs/箱(box)				
单价 unit price					