



产品性能 Product performance

|                                    |                                   |
|------------------------------------|-----------------------------------|
| 产品型号<br>Product model              | BEM-41F-1Z-C4-1-V                 |
| 形式<br>form                         | 1 NO                              |
| 控制电压<br>control voltage            | 250VAC 6A                         |
| 控制电流<br>control current            | 5-20mA                            |
| 负载电压<br>load voltage               | DC: 5-6VDC ; AC: 40-300VAC        |
| 负载电流<br>load current               | DC: 2A ; AC: 2A                   |
| 通态降压<br>On-state step-down         | DC: $\leq 1.2$ ; AC: $\leq 1.6V$  |
| 通断时间<br>On-off time                | DC: $\leq 5S$ ; AC: $\leq 10S$    |
| 断态漏电流<br>Off-state leakage current | DC: $\leq 5S$ ; AC: $\leq 10S$    |
| 介质耐压<br>Dielectric strength        | $\geq 1500VAC$                    |
| 使用环境<br>Use environment            | $-35 \sim +70^{\circ}C$           |
| 重量<br>weight                       | 1pcs/0.032KG 20pcs/1盒(box)0.698KG |
| 价格<br>the price                    |                                   |

外形尺寸及线路图 Dimensions and Wiring Diagram

