

导轨式开关电源系列

Rail type switching power supply series

BERM® 贝尔美



型号/model	MDR-10-5	MDR-10-12	MDR-10-15	MDR-10-24
性能/performance				
直流电压 DC voltage	5V	12V	15V	24V
额定电流 Rated current	0~2A	0~0.84A	0~0.6A	0~0.42A
额定功率 rated power	10W	10W	10W	10W
波纹与噪音 Ripple and noise	80mVp-p	120mVp-p	120mVp-p	150mVp-p
进线稳定度 Incoming line stability	±1%	±1%	±1%	±1%
负载稳定度 Load stability	±1%	±1%	±1%	±1%
效率 Suburban rate	76%	80%	81%	84%
直流电压可调范围 DC voltage adjustable range	±2%	±1%	±1%	±1%
输入电压范围 Input voltage range	100-240VAC 50/60Hz			
冲击电流 impact current	冷启动电流 20A/115VAC 40A/230VAC Cold start current			
过载保护 Overload protection	105%~160% 切断输出, 自动恢复 105%~160% cut off the output, automatic recovery			
自动、上升、保持时间 Auto, rise, hold time	500mS、30mS、/230VAC 1000mS、30mS/115VAC 满负载/Full load			
工作温度 Operating temperature	-10~+50°C			
尺寸 size	22.5X90X100mm (L*W*H)			
重量 weight	1pcs/0.19KG 90pcs/箱(box)			
单价 unit price				



型号/model	MDR-20-5	MDR-20-12	MDR-20-15	MDR-20-24
性能/performance				
直流电压 DC voltage	5V	12V	15V	24V
额定电流 Rated current	0~4A	0~1.67A	0~1.34A	0~1A
额定功率 rated power	20W	20W	20W	20W
波纹与噪音 Ripple and noise	80mVp-p	120mVp-p	120mVp-p	150mVp-p
进线稳定度 Incoming line stability	±1%	±1%	±1%	±1%
负载稳定度 Load stability	±1%	±1%	±1%	±1%
效率 Suburban rate	76%	80%	81%	84%
直流电压可调范围 DC voltage adjustable range	±2%	±1%	±1%	±1%
输入电压范围 Input voltage range	100-240VAC 50/60Hz			
冲击电流 impact current	冷启动电流 20A/115VAC 40A/230VAC Cold start current			
过载保护 Overload protection	105%~160% 切断输出, 自动恢复 105%~160% cut off the output, automatic recovery			
自动、上升、保持时间 Auto, rise, hold time	500mS、30mS、/230VAC 1000mS、30mS/115VAC 满负载/Full load			
工作温度 Operating temperature	-10~+50°C			
尺寸 size	22.5X90X100mm (L*W*H)			
重量 weight	1pcs/0.19KG 90pcs/箱(box)			
单价 unit price				