


LNE-WS塑料波纹管

PLASTIC CORRUGATED PIPE



△说明 Product Description

- Colour: WS-PE Type Black Grey
- Material: PA、PE、PP
- Characteristic: Flexibility is high, andle to bear rubing, able to bear suspending schooling to corrodes, fire-retardanting
- Temperature range: -20°C~+100°C
- Range of application: Instrument、switch board、device fabrication、project are installed、automobile line bunch

名称	软管规格	内径×外径(mm)	包装单位(米)
PE软管	AD10.0	6.5×10.0	100
	AD13.0	10.0×13.0	100
	AD15.8	12.0×15.8	100
	AD18.5	14.3×18.5	100
	AD21.2	17.0×21.2	100
	AD25.0	20.0×25.0	50
	AD28.5	23.0×28.5	50
	AD34.5	29.0×34.5	50
	AD42.5	36.0×42.5	50
	AD54.5	48.0×54.5	25
PP软管 (阻燃)	AD10.0	6.5×10.0	100
	AD13.0	10.0×13.0	100
	AD15.8	12.0×15.8	100
	AD18.5	14.3×18.5	100
	AD21.2	17.0×21.2	100
	AD25.0	20.0×25.0	50
	AD28.5	23.0×28.5	50
	AD34.5	29.0×34.5	50
	AD42.5	36.0×42.5	50
	AD54.5	48.0×54.5	25
PA软管 (尼龙阻燃)	AD10.0	6.5×10.0	100
	AD13.0	10.0×13.0	100
	AD15.8	12.0×15.8	100
	AD18.5	14.3×18.5	100
	AD21.2	17.0×21.2	100
	AD25.0	20.0×25.0	50
	AD28.5	23.0×28.5	50
	AD34.5	29.0×34.5	50
	AD42.5	36.0×42.5	50
	AD54.5	48.0×54.5	25