



CJB2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)
01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)
11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current
09:9A 25:25A 50:50A 95:95A
12:12A 32:32A 65:65A
18:18A 40:40A 80:80A

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	9A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	25A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	100万次 1 million times	机械寿命 Mechanical life	1000万次 10 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/0.361KG 50pcs/1箱(box)		
产品型号 Product number	CJB2-0910	CJB2-0901	
单价 unit price			



CJB2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)
01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)
11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current
09:9A 25:25A 50:50A 95:95A
12:12A 32:32A 65:65A
18:18A 40:40A 80:80A

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	12A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	25A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	100万次 1 million times	机械寿命 Mechanical life	1000万次 10 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/0.360KG 50pcs/1箱(box)		
产品型号 Product number	CJB2-1210	CJB2-1201	
单价 unit price			



CJX2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)

01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)

11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current

09:9A	25:25A	50:50A	95:95A
12:12A	32:32A	65:65A	
18:18A	40:40A	80:80A	

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	18A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	32A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	100万次 1 million times	机械寿命 Mechanical life	1000万次 10 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/0.373KG 50pcs/1箱(box)		
产品型号 Product number	CJX2-1810	CJX2-1801	
单价 unit price			



CJX2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)

01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)

11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current

09:9A	25:25A	50:50A	95:95A
12:12A	32:32A	65:65A	
18:18A	40:40A	80:80A	

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	25A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	40A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	100万次 1 million times	机械寿命 Mechanical life	1000万次 10 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/0.544KG 50pcs/1箱(box)		
产品型号 Product number	CJX2-2510	CJX2-2501	
单价 unit price			



CJX2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)

01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)

11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current

09:9A	25:25A	50:50A	95:95A
12:12A	32:32A	65:65A	
18:18A	40:40A	80:80A	

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	32A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	50A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	80万次 800,000 times	机械寿命 Mechanical life	800万次 8 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/0.559KG 50pcs/1箱(box)		
产品型号 Product number	CJX2-3210	CJX2-3201	
单价 unit price			



CJX2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)

01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)

11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current

09:9A	25:25A	50:50A	95:95A
12:12A	32:32A	65:65A	
18:18A	40:40A	80:80A	

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	40A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	60A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	80万次 800,000 times	机械寿命 Mechanical life	800万次 8 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/1.196KG 20pcs/1箱(box)		
产品型号 Product number	CJX2-4011		
单价 unit price			



CJX2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)
01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)
11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current
09:9A 25:25A 50:50A 95:95A
12:12A 32:32A 65:65A
18:18A 40:40A 80:80A

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	50A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	70A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	60万次 600,000 times	机械寿命 Mechanical life	800万次 8 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/1.196KG 20pcs/1箱(box)		
产品型号 Product number	CJX2-5011		
单价 unit price			



CJX2 - □□□□

品牌型号
Brand model number

触点数量
Contact Quantity

交流接触器/AC contactor

10表示三常开主触头、一常开辅助触点(32A及以下)
Represents three normally open main contacts, one normally open auxiliary contact (32A and below)
01表示三常开主触头、一常闭辅助触点(32A及以下)
Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)
11表示三常开主触头、一常开一常闭辅助触点(40A及以上)
means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)

额定电流/Rated current
09:9A 25:25A 50:50A 95:95A
12:12A 32:32A 65:65A
18:18A 40:40A 80:80A

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)		
额定电流 Rated current	65A	额定绝缘电压 Rated insulation voltage	690V
发热电流 Heating current	80A	额定冲击耐受电压 Rated shock withstand voltage	6KV
电气寿命 Electrical life	60万次 600,000 times	机械寿命 Mechanical life	800万次 8 million times
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10
周围空气温度 Ambient air temperature	-5°C~+40°C, 24小时内其平均温度不超过+35°C -5°C~+40°C, the average temperature within 24 hours does not exceed +35°C		
重量 weight	1pcs/1.199KG 20pcs/1箱(box)		
产品型号 Product number	CJX2-6511		
单价 unit price			



CJX2 - □□□□

交流接触器/AC contactor

品牌型号 Brand model number	触点数量 Contact Quantity	10表示三常开主触头、一常开辅助触点(32A及以下) Represents three normally open main contacts, one normally open auxiliary contact (32A and below)
		01表示三常开主触头、一常闭辅助触点(32A及以下) Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)
额定电流/Rated current		11表示三常开主触头、一常开一常闭辅助触点(40A及以上) means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)
		09:9A 25:25A 50:50A 95:95A 12:12A 32:32A 65:65A 18:18A 40:40A 80:80A

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)			
额定电流 Rated current	80A	额定绝缘电压 Rated insulation voltage	690V	
发热电流 Heating current	100A	额定冲击耐受电压 Rated shock withstand voltage	6KV	
电气寿命 Electrical life	60万次 600,000 times	机械寿命 Mechanical life	600万次 6 million times	
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide	
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10	
周围空气温度 Ambient air temperature	-5℃~+40℃,24小时内其平均温度不超过+35℃ -5℃~+40℃, the average temperature within 24 hours does not exceed +35℃			
重量 weight	1pcs/1.438KG 20pcs/1箱(box)			
产品型号 Product number	CJX2-8011			
单价 unit price				



CJX2 - □□□□

交流接触器/AC contactor

品牌型号 Brand model number	触点数量 Contact Quantity	10表示三常开主触头、一常开辅助触点(32A及以下) Represents three normally open main contacts, one normally open auxiliary contact (32A and below)
		01表示三常开主触头、一常闭辅助触点(32A及以下) Represents three normally open main contacts, one normally closed auxiliary contact (32A and below)
额定电流/Rated current		11表示三常开主触头、一常开一常闭辅助触点(40A及以上) means three normally open main contacts, one normally open and one normally closed auxiliary contact (40A and above)
		09:9A 25:25A 50:50A 95:95A 12:12A 32:32A 65:65A 18:18A 40:40A 80:80A

线圈电压 Coil voltage	AC24V AC36V AC48V AC110V AC220V AC380V (50/60Hz)			
额定电流 Rated current	95A	额定绝缘电压 Rated insulation voltage	690V	
发热电流 Heating current	125A	额定冲击耐受电压 Rated shock withstand voltage	6KV	
电气寿命 Electrical life	60万次 600,000 times	机械寿命 Mechanical life	600万次 6 million times	
触点材质 Contact material	银触点 Silver contacts	导件材质 Guide material	黄铜导件 Brass Guide	
线圈材质 Coil material	全铜线圈 Copper coil	防护等级 Protection level	IP 10	
周围空气温度 Ambient air temperature	-5℃~+40℃,24小时内其平均温度不超过+35℃ -5℃~+40℃, the average temperature within 24 hours does not exceed +35℃			
重量 weight	1pcs/1.442KG 20pcs/1箱(box)			
产品型号 Product number	CJX2-9511			
单价 unit price				